

DECLARATION OF PERFORMANCE

No. 015

Unique identification code of the type selection: STANDARD_70_01/015

Intended use: Single-sash window of the VEKA Perfectline Standard 70 mm system made from unplasticized

PVC profiles, designed for use in residential and commercial locations.

Manufacturer: WIKĘD Sp. z o.o. Sp. k., ul. Wielki Las 19, 84-242 Luzino

Assessment and verification system of performance consistency: System 3

Harmonized standard: PN-EN 14351-1+A2:2016-10

Notified body: Mobile Construction Technology Laboratory Sp. z o.o., Notification No. 2189

ESSENTIAL CHARACTERISTICS	DECLARED PERFORMANCE		HARMONIZED TECHNICAL SPECIFICATION	
Wind load resistance	Class C4		PN-EN 14351-1+A2:2016- 10	
Water tightness	E900		PN-EN 14351-1+A2:2016- 10	
Hazardous substances	npd*		PN-EN 14351-1+A2:2016- 10	
Load-bearing capacity of safety devices	350N (threshold value)		PN-EN 14351-1+A2:2016- 10	
Acoustic properties	Surface up to 2.7 m ²	34dB (-1, -4)	PN-EN 14351-1+A2:2016-	
	Surface from 2.7 m ² to 3.6 m ²	33dB (-1, -4)		
	Surface from 3.6 m ² to 4.6 m ²	32dB (-1, -4)		
	Surface above 4.6 m ²	31dB (-1, -4)		
Thermal transmittance	Uw=1,1 W/m ² •K**		PN-EN 14351-1+A2:2016-	
	Uw=1,0 W/m ² •K***		PN-EN 14351-1+A2:2016- 10	
Solar radiation properties				
Solar factor	53%		PN-EN 14351-1+A2:2016-	
Light transmittance	74%		PN-EN 14351-1+A2:2016- 10	
Air permeability	Class 4		PN-EN 14351-1+A2:2016- 10	

^{*} No Performance Declared

- Installing air inlets changes the thermal transmittance coefficient of the joinery.
- Using decorative elements between the panes changes the thermal properties of the glazing unit.
- The order specification may limit the declared parameters.

The performance of the product described above is in conformity with the declared set of performance characteristics. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer mentioned above.

^{**} Value determined for a reference window size of 1230x1480 mm with glazing 4/12/4/12/4:

^{***} Value determined for a reference window size of 1230x1480 mm with glazing 4/12/4/12/4 and TGI-Spacer M between-glass spacer frame.

Signed on behalf of the manufacturer

© ul. Wielki Las 19, 84 % (58) 678 01 77 / (58 ⇔ 105 00 00 77 / (58

WIKED Sp. z o.o. Sp. k. © ul. Wielki Las 19, 84-242 Luzino % (58) 678 0177 / (58) 678 00 98 ओ NIP 588-20-15-465 REGON 192759440

inż. Paweł Rutkowski Luzino, 25.02.2019