

## NATIONAL DECLARATION OF PERFORMANCE

No. ALU/ZEW/2021/7

- 1. Unique identification code of the product type:
- PE68/68HI/ZEW/2021/7
  2. Intended use:

Single or double-sash doors of the Procural PE68/68HI system, opening outward or inward, designed for communication in residential and commercial locations.

- 3. Manufacturer WIKĘD Sp. z o.o. Sp. komandytowa, ul. Wielki Las 19, 84-242 Luzino
- 4. Authorized representative:
- 5. System(s) of assessment and verification of constancy of performance: System 3
- 6a. Harmonized standard: EN-14351-1:2006+A2:2016 Notified body: Building Research Institute, Notification No. 1488
- 6b. European assessment document:

European technical assessment:

Technical assessment body:

Notified body:

7. Declared performance:

| ESSENTIAL CHARACTERISTICS               | DECLARED PERFORMANCE | HARMONIZED TECHNICAL SPECIFICATION |
|---|----------------------|------------------------------------|
| Wind load resistance                    | C2/B3                | EN 14351-1:2006+A2:2016            |
| Water tightness                         | 7A                   |                                    |
| Hazardous substances                    | npd*                 |                                    |
| Impact resistance                       | 3                    |                                    |
| Load-bearing capacity of safety devices | npd*                 |                                    |
| Height                                  | Requirements met     |                                    |
| Release capability                      | npd*                 |                                    |
| Acoustic properties                     | npd*                 |                                    |
| Thermal transmittance (Ud)**            |                      |                                    |
| Single-sash PE68                        | Ud = 1.1 W/m²•K      |                                    |
| Double-sash PE68HI                      | Ud = 1.2 W/m²•K      |                                    |
| Solar radiation properties              | npd*                 |                                    |
| Air permeability                        | Class 3              |                                    |
| Vertical load resistance                | Class 4/3            |                                    |
| Static torsion resistance               | Class 4/3            |                                    |
| Operating forces                        | Class 2              |                                    |

\*npd: No Performance Declared \*\* Values determined for a reference structure with external dimensions of 1600x2780mm, using a glazing unit 1T/16ArCHU/4/16ArCHU/33.1T and Chromatech Ultra spacer bar.

8. Appropriate technical documentation or special technical documentation:

The performance of the product specified above is in conformity with the declared set of performance characteristics. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer mentioned above.

Signed on behalf of the manufacturer:



Marcin Dembiński Head of Research and Certification Department, WIKĘD Luzino, 13.06.2023